7

Snow Load Report

1. Roof and Building Data

Ground Snow Load (Pg): 100.0 psf Roof Pitch: 5 /12 Risk Category: II Eave-to-Ridge (W): 21 ft. Terrain Category: C Exposure: Partially Exposed Thermal Factor (C_t): 1.00 Roof Surface: Metal Roof System: Common Truss

Spacing: 48 in. o/c Overhang: 12 in.

2. Design Loads

Top Chord Dead Load: 5 psf Bottom Chord Dead Load: 5 psf

SF (Slope Factor) = $1/\text{Cosine}(\Phi) = 1.08$ (Dead loads specified on a projected horizontal basis take into account the effect of the pitch via a slope factor.)

Adj. TCDL (TCDL x SF): 5.4 psf

3. Design Assumptions

Code Standard: ASCE 7-10 Number of Plies: 1 PLY Bottom Chord Pitch: 0 /12

4. Snow Load Calculations

Calculate flat roof snow load pf using the following equation:

 $p_f = 0.7C_eC_tI_sp_g$

where:

 p_f = Flat Roof Snow Load in psf

C_e = 1.00 = Exposure Factor, as determined by ASCE 7-10 Table 7-2 (Terrain Cat. C, Exp. Partially Exposed)

 $C_t = 1.00 = Thermal Factor$, as determined by ASCE 7-10 Table 7-3

 $I_s = 1.00 = \text{Importance Factor}$, as determined by ASCE 7-10 Table 1.5-2 (Risk Cat. II)

 $p_g = 100.0 \text{ psf} = Ground Snow Load in psf}$

 $p_f = 0.7C_eC_tI_sp_g = 0.7(1.00)(1.00)(1.00)(100.0) = 70.0 \text{ psf}$

Subject	Customer	Location		Job No.
Snow Loads				2025A169
Cedric Green, PE	Driftwood Desig	n	This report may not be copied, reproduced or distributed without the written consent of Driftwood Design, LLC	Rev.
Date 4/24/2025	305 N 2nd St ph. 7853176354 www.driftv	wood3d.com DRIFTWOOD	Copyright © 2025	Page 1

A minimum roof snow load, pm shall apply to monoslope, hip and gable roofs with slopes less than 15 degrees using the following equations:

Where p_g is 20 psf or less: $p_m=I_sp_g$ Where p_g exceeds 20 psf: $p_m=I_s(20)$

Roof slope is greater than 15 degrees, the minimum roof snow load, pm, does not apply.

For locations where pg is 20 psf or less, but not zero, all roofs with slopes (in degrees) less than W/50 with W in feet shall included a 5 psf rain-on-snow surcharge load. This additional load applies only to the sloped roof (balanced) load case and need not be used in combination with drift, sliding, unbalanced, minimum, or partial loads.

Roof slope in degrees (22.62°) is greater than W/50 = 0.4, the 5.0 psf rain-on-snow surcharge load does not apply.

Calculate sloped roof snow load ps using the following equation:

 $p_s = C_s p_f$

where:

 p_s = Sloped Roof Snow Load in psf C_s = 1-[(22.62-5)/65] = 0.73 = Roof Slope Factor, as determined by ASCE 7-10 Sec. 7.4.1-7.4.4 and Figure 7-2 p_f = Flat Roof Snow Load in psf

Roof surface (Metal) is considered a "slippery" roof. For a $C_t = 1.00$ the roof slope factor C_s is given by the dashed line of ASCE 7-10 Figure 7-2a.

$$p_s = C_s p_f = (0.73)(70.0) = 51.0 \text{ psf}$$

Calculate unbalanced snow load for hip and gable roofs as shown in ASCE 7-10 Figure 7-5.

Unbalanced snow loads are required for roof pitches between 1/2 on 12 to 7 on 12.

Using the following equations:

$$\gamma = 0.13p_g + 14 \text{ (snow density)}$$

$$h_d = .43\sqrt[3]{l_u}\sqrt[4]{p_g + 10} - 1.5 \text{ (drift height) [if } l_u < 20 \text{ ft., use } l_u = 20 \text{ ft.]}$$

$$l_d = \frac{8}{3}h_d\sqrt{S} \text{ (width of drift surcharge)}$$

$$p_d = h_d\gamma / \sqrt{S} \text{ (drift surcharge snow load)}$$

where:

 γ = Snow density in pcf, not to exceed 30 pcf.


 h_d = Drift height in feet, as determined by eqn. or ASCE 7-10 Fig. 7-9.

 $l_u = W = Ridge$ to eave distance in feet, windward side of roof.

S = 12/Roof Pitch

l_d = Width of drift surcharge in feet.

pd = Drift Surcharge Snow Load in psf



Subject	Customer	Location		Job No.
Snow Loads				2025A169
Cedric Green, PE	Driftwood Desig	n	This report may not be copied, reproduced or distributed without the written consent of Driftwood Design, LLC	Rev.
Date 4/24/2025	305 N 2nd St ph. 7853176354 www.driftw	wood3d.com DRIFTWOOD	Copyright © 2025	Page 2

$$p_{windward} = 0.3p_s = (0.3)(51.0) = 15.3 \text{ psf}$$

 $p_{leeward} = p_s = 51.0 \text{ psf}$
 $\gamma = 0.13(100.0) + 14 = 27.00 \text{ pcf}$


$$h_d = .43\sqrt[3]{21}\sqrt[4]{100.0 + 10} - 1.5$$
 = 2.34 ft. [l_u = 21 ft.]

$$l_d = \frac{8}{3} \times 2.34 \times \sqrt{12/5} = 9.68 \text{ ft.}$$

$$p_d = \frac{2.34 \times 27.00}{\sqrt{12/5}} = 40.8 \text{ psf}$$


On warm roofs apply a distributed $2p_f$ snow load on all overhanging portions as per ASCE 7-10 section 7.4.5. No other loads except dead loads shall be present on the roof when this uniformly distributed load is applied.

$$2p_f = (2)(70.0) = 140.0 \text{ psf}$$




$$\begin{split} R_1 &= D + S = 855.0 \text{ lbs} + 4286.1 \text{ lbs} \\ R_2 &= D + S = 855.0 \text{ lbs} + 4286.1 \text{ lbs} \end{split}$$

Subject	Customer	Location		Job No.
Snow Loads				2025A169
Cedric Green, PE	Driftwood Design 305 N 2nd St ph. 7853176354 www.driftv	n	This report may not be copied, reproduced or distributed without the written consent of Driftwood Design, LLC	Rev.
Date 4/24/2025		wood3d.com DESIGN	Copyright © 2025	Page 3



 $R_1 = D + S = 855.0 \text{ lbs} + 2597.2 \text{ lbs}$ $R_2 = D + S = 855.0 \text{ lbs} + 4554.4 \text{ lbs}$



 $R_1 = D + S = 855.0 \text{ lbs} + 560.0 \text{ lbs}$ $R_2 = D + S = 855.0 \text{ lbs} + 560.0 \text{ lbs}$

Subject Snow Loads	Customer	Location			ор No. 2025A169
Cedric Green, PE	Driftwood Desig	n		This report may not be copied, reproduced or distributed without the written consent of Driftwood Design, LLC	Rev.
Date 4/24/2025	305 N 2nd St ph. 7853176354 www.driftv	wood3d.com	DRIFT/VOOD DESIGN	Copyright © 2025	Page 4